

**X-100** 6A20.80  
S1P SRC ESD

**ACTION**  
LINE | X-1

SIZES 36 - 48

**X-BALANCE PRO**

The precise foothold for stability.

**CARBON PRO**

Best conductive foam for maximum performance with lighter and high impulse properties.



**FLYKNIT**

Flyknit technology uses high-strength fibers to create lightweight uppers with targeted areas of support, elasticity and breathability.

**ALUMINIUM TOE CAP**

Lightweight toe cap able to resist against pressure up to 200 Joules. Rubber coating for extra protection and easy cleaning.

**FLOAT**

The high tenacity fabrics for zero perforation give strong flexibility and lightness.



**HARD STICKY PU**

Strategically positioned in the areas of most wear, to increase durability.

**CLEATS**

Open cleats for a better fluid dispersion.

**DOUBLE DENSITY PU SOLE**

This sole blends two different PU densities, where the midsole is extremely soft and comfortable, while the hard PU outsole provides great grip and resistance to oil and abrasion.



ALUMINIUM TOE CAP



FLOAT INSOLE



ELETROSTATIC DISCHARGE

X-BALANCE PRO

**NORMS** EN ISO 20345:2011

**S1P** - Closed heel area with the following characteristics:

- E** - Heel energy absorption
- A** - Antistatic footwear
- FO** - Resistance to fuel oil of the outsole
- P** - Penetration resistance sole

**ADDITIONAL CHARACTERISTICS:**

- SRC** - Slip resistance on ceramic + sodium lauryl sulfate and steel + glycerin
- ESD** - Electrostatic Discharge (EN 61340-5-1)

**ADVANTAGES**

- Light | Comfortable | Breathable | Versatile | Sporty Look | Excellent anti-slip characteristics

**WORKING ENVIRONMENT**

- Indoor Jobs | Logistics | Administrative | Shopkeeper | Warehouse